



SECTION A-A

NOTES:

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3. TOOL # WD 20342 R3

$A_p = 2.70\text{MM} [0.106]$
$B_p = 13.25\text{MM} [0.522]$
$K_p = 8.50\text{MM} [0.335]$
$K_j = 6.50\text{MM} [0.256]$

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY W HARRISON	DATE 10-Dec-02
±	CHECKED BY .	DATE .
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	--- CONFIDENTIALITY ---	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY Accutech AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH Accutech WRITTEN CONSENT.	
$\nabla \pm 0.5^\circ$	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND Accutech DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN MM	SCALE: NTS	
	SHEET OF	

AccuTechPlastics	
THIRD ANGLE PROJECTION	
TITLE/DESCRIPTION TAPE - CARR 3 PIN SMT 24mm	
PART NO./I.D. NO.	CT-9924H-138
MATERIAL/MOLD NO.	STATIC DISSIPATIVE POLYSTYRENE
DRAWING NO.	01-019805

A SIZE
APPD. BY

X-329

ECO NO.
REV.
A