



NOTES:

- EIA-481 STANDARDS APPLY
- POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
- DIE # WD20452

Ao	12.280 [0.483]
Bo	15.810 [0.622]
Ko	2.350 [0.093]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 16-Jan-03
±	CHECKED BY R. BAKER	DATE 16-Jan-03
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	--- CONFIDENTIALITY ---	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY <b>Accutech</b> AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH <b>Accutech</b> WRITTEN CONSENT.	
± 0.5°	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND <b>Accutech</b> DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN MM	SCALE: NTS	
SHEET OF	1	

THIRD ANGLE PROJECTION

TITLE/DESCRIPTION  
TAPE - CARR  
R2265 T-R 24mm

PART NO./I.D. NO.  
CT-9924H-163

MATERIAL/MOLD NO.  
STATIC DISSIPATIVE  
POLYSTYRENE

DRAWING NO.  
01-020315

**A** SIZE

APPD. BY

X-569

ECO NO.  
REV.  
A