



NOTES:

- EIA-481 STANDARDS APPLY
- POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
- $P_{10} = P_0 \times 10$
- DIE # WD20443 RI

$A_0$	12.820 [0.505]
$B_0$	17.960 [0.707]
$K_0$	3.450 [0.136]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 07-Feb-03
$\pm$	CHECKED BY .	DATE .
$\pm$	DESIGNED BY .	DATE .
$\pm$	APPROVED BY .	DATE .
$\pm$	--- CONFIDENTIALITY --- THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY <b>Accutech</b> AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH <b>Accutech</b> WRITTEN CONSENT.	
DRAFT UNLESS NOTED: 0.5°	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND <b>Accutech</b> DRAFTING STANDARD NO. 1.0000.	
$\nabla \pm 0.5^\circ$	ALL DIMENSIONS ARE IN MM	
SCALE: NTS	SHEET OF 1	

		A SIZE APPD. BY
THIRD ANGLE PROJECTION		X-2758
TITLE/DESCRIPTION TAPE - CARR 50-218 32mm		
PART NO./I.D. NO. CT-9932H-150		
MATERIAL/MOLD NO. STATIC DISSIPATIVE POLYSTYRENE		
DRAWING NO. 01-020053		ECO NO. REV. B