



NOTES:

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3. DIE # WD20449

A ₀	14.150 [0.557]
B ₀	19.670 [0.774]
K ₀	2.350 [0.093]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 16-Jan-03
±	CHECKED BY R. BAKER	DATE 16-Jan-03
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	--- CONFIDENTIALITY --- THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY Accutech AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH Accutech WRITTEN CONSENT.	
DRAFT UNLESS NOTED: 0.5°	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND Accutech DRAFTING STANDARD NO. 1.0000.	
± 0.5°	ALL DIMENSIONS ARE IN MM	
SCALE: NTS	SHEET OF 1	

THIRD ANGLE PROJECTION	
TITLE/DESCRIPTION TAPE - CARR R2263 T-R 32mm	
PART NO./I.D. NO.	CT-9932H-160
MATERIAL/MOLD NO.	STATIC DISSIPATIVE POLYSTYRENE
DRAWING NO.	01-020312

A SIZE
APPD. BY

X-569
ECO NO.
REV.
A