



SECTION A-A

- NOTES:**
1. EIA-481 STANDARDS APPLY
  2. MATERIAL: STATIC DISSIPATIVE STYRENE
  3. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
  4. DIE # WD20407

<b>A</b>	<b>= 28.30MM [1.114]</b>
<b>B</b>	<b>= 28.50MM [1.122]</b>
<b>K</b>	<b>= 2.11MM [0.083]</b>

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. Wagner	DATE 21-Oct-02
±	CHECKED BY .	DATE .
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	<b>--- CONFIDENTIALITY ---</b>	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY <b>Accutech</b> AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH <b>Accutech</b> WRITTEN CONSENT.	
$\nabla \pm 0.5^\circ$	<b>UNLESS OTHERWISE NOTED:</b> ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND <b>Accutech</b> DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN mm	SCALE: NTS	
	SHEET OF 1	

		A SIZE
THIRD ANGLE PROJECTION		APPD. BY
TITLE/DESCRIPTION TAPE - CARR R2167A 44mm		85461
PART NO./I.D. NO. CT-9944H-119		
MATERIAL/MOLD NO. STATIC DISSIPATIVE POLYSTYRENE		
DRAWING NO. 01-019203		
		ECO NO. REV. A