



DETAIL A  
SCALE 4.000

SECTION A-A

- NOTES:**
- EIA-481 STANDARDS APPLY
  - POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE.
  - DIE # WD00091 RI

Ao	35.00 [1.378]
Bo	36.78 [1.448]
Ko	5.40 [.213]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 13-Jan-03
±	CHECKED BY R. BAKER	DATE 13-Jan-03
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	<b>--- CONFIDENTIALITY ---</b>	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY <b>Accutech</b> AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH <b>Accutech</b> WRITTEN CONSENT.	
± 0.5°	<b>UNLESS OTHERWISE NOTED:</b> ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND <b>Accutech</b> DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN MM	SCALE: NTS	
SHEET OF	1 1	

		A SIZE APPD. BY
THIRD ANGLE PROJECTION		119-X ECO NO. REV. B
TITLE/DESCRIPTION TAPE - CARR R1908A T-R 56mm		
PART NO./I.D. NO. CT-9956H-143		
MATERIAL/MOLD NO. STATIC DISSIPATIVE POLYSTYRENE		
DRAWING NO. 01-019961		