



SECTION A-A

- NOTES:
 1. EIA-481 STANDARDS APPLY
 2. MATERIAL: STATIC DISSIPATIVE STYRENE
 3. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
 4. DIE # WD10305

$A_p = 18.66\text{MM} [0.735]$
$B_p = 49.56\text{MM} [1.951]$
$K_p = 4.55\text{MM} [0.179]$

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. Wagner	DATE 21-Oct-02
±	CHECKED BY .	DATE .
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	--- CONFIDENTIALITY --- THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY Accutech AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH Accutech WRITTEN CONSENT.	
DRAFT UNLESS NOTED: 0.5°	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND Accutech DRAFTING STANDARD NO. 1.0000.	
± 0.5°	SCALE: NTS	
ALL DIMENSIONS ARE IN mm	SHEET OF	

AccuTechPlastics	
THIRD ANGLE PROJECTION	
TITLE/DESCRIPTION TAPE - CARR R2118. 72mm	
PART NO./I.D. NO.	CT-9972H-087
MATERIAL/MOLD NO.	STATIC DISSIPATIVE POLYSTYRENE
DRAWING NO.	01-019211

A SIZE
 APPD. BY
 X-394
 ECO NO.
 REV.
 B