



- NOTES:**
1. EIA-481 STANDARDS APPLY
 2. MATERIAL: STATIC DISSIPATIVE STYRENE
 3. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
 4. $P10 = P0 \times 10$
 5. DIE # WD10242

$A_0 = 12.50\text{MM} [0.492]$
$B_0 = 18.70\text{MM} [0.736]$
$K_p = 3.30\text{MM} [0.130]$
$K_r = 2.70\text{MM} [0.106]$

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 17-Dec-02
±	CHECKED BY R. BAKER	DATE 17-Dec-02
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	--- CONFIDENTIALITY ---	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY Accutech AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH Accutech WRITTEN CONSENT.	
± 0.5°	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND Accutech DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN MM	SCALE: NTS	
SHEET OF		

		A SIZE APPD. BY
THIRD ANGLE PROJECTION		X-1367
TITLE/DESCRIPTION TAPE - CARR SOIC-28xWLP 24mm		
PART NO./I.D. NO. CT00004-H-A0054		ECO NO. REV.
MATERIAL/MOLD NO. STATIC DISSIPATIVE POLYSTYRENE		
DRAWING NO. 01-019942		C