



SECTION A-A

**NOTES:**

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE.
3.  $P10 = P_0 \times 10$
4. DIE # WD10206

Ao	12.95 [.510]
Bo	12.95 [.510]
Ko	4.90 [.193]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 08-Jan-03		<b>A</b> SIZE APPD. BY
±	CHECKED BY R. BAKER	DATE 08-Jan-03		
±	DESIGNED BY .	DATE .		
±	APPROVED BY .	DATE .		
±	--- CONFIDENTIALITY ---		THIRD ANGLE PROJECTION	X-1367
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY <b>Accutech</b> AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH <b>Accutech</b> WRITTEN CONSENT.		TITLE/DESCRIPTION TAPE - CARR PLCC28 24mm	
± 0.5°			PART NO./I.D. NO. CT00008-H-A0045	
ALL DIMENSIONS ARE IN MM			MATERIAL/MOLD NO. STATIC DISSIPATIVE POLYSTYRENE	
SCALE: NTS	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND <b>Accutech</b> DRAFTING STANDARD NO. 1.0000.		DRAWING NO. 01-020064	
SHEET OF				