



**NOTES:**

- EIA-481 STANDARDS APPLY
- POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
- $P_{10} = P_0 \times 10$
- DIE # WD10219

A <sub>0</sub>	17.98 [.708]
B <sub>0</sub>	17.98 [.708]
K <sub>0</sub>	4.90 [.193]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 06-Jan-03
±	CHECKED BY R. BAKER	DATE 06-Jan-03
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	<b>--- CONFIDENTIALITY ---</b>	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY <b>Accutech</b> AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH <b>Accutech</b> WRITTEN CONSENT.	
± 0.5°		
ALL DIMENSIONS ARE IN MM		
SCALE: NTS	<b>UNLESS OTHERWISE NOTED:</b> ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND <b>Accutech</b> DRAFTING STANDARD NO. 1.0000.	
1 SHEET OF 1		

<b>AccuTechPlastics</b>		<b>A</b> SIZE APPD. BY
THIRD ANGLE PROJECTION		X-1252
TITLE/DESCRIPTION TAPE - CARR PLCC-44F 32mm		
PART NO./I.D. NO. CT00013-H-A0040		
MATERIAL/MOLD NO. STATIC DISSIPATIVE POLYSTYRENE		
DRAWING NO. 01-020067		ECO NO. REV. <b>B</b>