



NOTES:

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3. $P10 = P_0 \times 10$
4. DIE # WD10262

A ₀	18.00 [.709]
B ₀	18.00 [.709]
K ₀	5.10 [.201]
K ₁	4.20 [.165]

TOLERANCES UNLESS OTHERWISE SPECIFIED	
±	
±	
±	
±	
DRAFT UNLESS NOTED: 0.5°	
± 0.5°	
ALL DIMENSIONS ARE IN MM	
SCALE: NTS	
SHEET OF	

DRAWN BY K. WAGNER	DATE 14-Nov-02
CHECKED BY R. BAKER	DATE 22-Nov-02
DESIGNED BY .	DATE .
APPROVED BY .	DATE .
--- CONFIDENTIALITY ---	
THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY Accutech AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH Accutech WRITTEN CONSENT.	
UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND Accutech DRAFTING STANDARD NO. 1.0000.	

Accu-Tech Plastics	
THIRD ANGLE PROJECTION	
TITLE/DESCRIPTION TAPE - CARR PLCC-44P 32mm	
PART NO./I.D. NO.	CT00014-G-A0038
MATERIAL/MOLD NO.	STATIC DISSIPATIVE POLYSTYRENE
DRAWING NO.	01-019539

A SIZE
 APPD. BY
 X-1252
 ECO NO.
 REV.
 B