



SECTION A-A

NOTES:

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE.
3. $P10 = P_0 \times 10$
4. DIE # WD10275

Ao	23.80 [.937]
Bo	23.80 [.937]
Ko	5.60 [.220]
K1	5.20 [.205]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 14-Nov-02
±	CHECKED BY R. BAKER	DATE 22-Nov-02
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	--- CONFIDENTIALITY ---	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY Accutech AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH Accutech WRITTEN CONSENT.	
± 0.5°	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND Accutech DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN MM		
SCALE: NTS		
SHEET OF		

Accu-Tech Plastics		A SIZE APPD. BY
THIRD ANGLE PROJECTION		X-1252
TITLE/DESCRIPTION TAPE - CARR PLCC-44SKT 44mm		ECO NO. REV.
PART NO./I.D. NO. CT00015-G-A0034		B
MATERIAL/MOLD NO. STATIC DISSIPATIVE POLYSTYRENE		
DRAWING NO. 01-019538		