



NOTES:

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE.
3. $P10 = P_0 \times 10$
4. DIE # WD10276

A ₀	26.20 [1.031]
B ₀	26.20 [1.031]
K ₀	5.60 [.220]
K ₁	5.20 [.205]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 15-Nov-02
±	CHECKED BY R. BAKER	DATE 10-Dec-02
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	--- CONFIDENTIALITY ---	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY Accutech AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH Accutech WRITTEN CONSENT.	
± 0.5°	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND Accutech DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN MM		
SCALE: NTS		
SHEET OF 1		

		A SIZE APPD. BY
THIRD ANGLE PROJECTION		X-1252 ECO NO. REV. B
TITLE/DESCRIPTION TAPE - CARR PLCC-52SKT 44mm		
PART NO./I.D. NO. CT00017-G-A0034		
MATERIAL/MOLD NO. STATIC DISSIPATIVE POLYSTYRENE		
DRAWING NO. 01-019549		