



**NOTES:**

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE.
3.  $P10 = P_0 \times 10$
4. DIE # WD00135

A <sub>0</sub>	25.60 [1.008]
B <sub>0</sub>	25.60 [1.008]
K <sub>0</sub>	5.30 [.209]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 18-Nov-02	<b>Accu-Tech Plastics</b>	THIRD ANGLE PROJECTION	APPD. BY <b>A</b> SIZE
±	CHECKED BY R. BAKER	DATE 10-Dec-02			
±	DESIGNED BY .	DATE .			
±	APPROVED BY .	DATE .			
±	--- CONFIDENTIALITY ---		TITLE/DESCRIPTION TAPE - CARR PLCC-68F 44mm	DRAWING NO. 01-019567	ECO NO. REV. <b>B</b>
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY <b>Accutech</b> AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH <b>Accutech</b> WRITTEN CONSENT.		PART NO./I.D. NO. CT00018-G-A0032		
$\nabla \pm 0.5^\circ$			MATERIAL/MOLD NO. STATIC DISSIPATIVE POLYSTYRENE		
ALL DIMENSIONS ARE IN MM	SCALE: NTS	SHEET OF 1	DRAWING NO. 01-019567		