



SECTION A - A

SEE DETAIL A

NOTES:

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE.
3. $P_{10} = P_0 \times 10$
4. DIE # WD10263

A ₀	25.60 [1.008]
B ₀	25.60 [1.008]
K ₀	5.80 [.228]
K ₁	4.20 [.165]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 19-Nov-02
±	CHECKED BY R. BAKER	DATE 10-Dec-02
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	--- CONFIDENTIALITY ---	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY Accutech AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH Accutech WRITTEN CONSENT.	
± 0.5°	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 Accutech DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN MM		
SCALE: NTS		
SHEET OF		

		A SIZE APPD. BY
THIRD ANGLE PROJECTION		X-1252 ECO NO. REV. B
TITLE/DESCRIPTION TAPE - CARR PLCC-68P 44mm		
PART NO./I.D. NO. CT00019-G-A0032		
MATERIAL/MOLD NO. STATIC DISSIPATIVE POLYSTYRENE		
DRAWING NO. 01-019580		