



**NOTES:**

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE.
3.  $P10 = P_0 \times 10$
4. DIE # WD10277

Ao	31.40 [1.236]
Bo	31.40 [1.236]
Ko	5.60 [.220]
KI	5.20 [.205]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 19-Nov-02
±	CHECKED BY R. BAKER	DATE 10-Dec-02
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	<b>--- CONFIDENTIALITY ---</b>	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY <b>Accutech</b> AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH <b>Accutech</b> WRITTEN CONSENT.	
± 0.5°	<b>UNLESS OTHERWISE NOTED:</b> ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND <b>Accutech</b> DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN MM		
SCALE: NTS		
SHEET OF		

THIRD ANGLE PROJECTION

TITLE/DESCRIPTION  
TAPE - CARR  
PLCC-68SKT 44mm

PART NO./I.D. NO.  
CT00020-G-A0032

MATERIAL/MOLD NO.  
STATIC DISSIPATIVE  
POLYSTYRENE

DRAWING NO.  
01-019581

**A** SIZE

APPD. BY

X-1252

ECO NO.  
REV.  
**B**