



SECTION A-A

NOTES:

1. EIA-481 STANDARDS APPLY
2. MATERIAL: STATIC DISSIPATIVE STYRENE
3. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
4.  $P10 = P_0 \times 10$
5. DIE # WD10259

$A_0 = 8.60\text{MM} [0.339]$
$B_0 = 11.50\text{MM} [0.453]$
$K_0 = 1.50\text{MM} [0.059]$
$K_1 = 1.10\text{MM} [0.043]$

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY R. Baker	DATE 01-Oct-02
±	CHECKED BY .	DATE .
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	--- CONFIDENTIALITY ---	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY Accutech AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH Accutech WRITTEN CONSENT.	
± 0.5°	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND Accutech DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN MM	SCALE: NTS	
SHEET OF		

THIRD ANGLE PROJECTION	
TITLE/DESCRIPTION TAPE-CARR TSSOP-32L (P) 24MM	
PART NO./I.D. NO.	CT00030-G-A0097
MATERIAL/MOLD NO.	STATIC DISSIPATIVE POLYSTYRENE
DRAWING NO.	01-018856

A  
SIZE  
APPD. BY

X-1386

ECO NO.  
REV.  
B