



SECTION A-A

- NOTES:**
1. EIA-481 STANDARDS APPLY
  2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
  3.  $P10 = P0 \times 10$
  4. DIE # WD10279

$A_0 =$	<b>8.50MM [0.335]</b>
$B_0 =$	<b>20.60MM [0.811]</b>
$K_0 =$	<b>2.10MM [0.083]</b>
$K_1 =$	<b>1.30MM [0.051]</b>

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY R. Baker	DATE 03-Oct-02
±	CHECKED BY .	DATE .
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	<b>--- CONFIDENTIALITY ---</b>	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY <b>Accutech</b> AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH <b>Accutech</b> WRITTEN CONSENT.	
± 0.5°	<b>UNLESS OTHERWISE NOTED:</b> ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND <b>Accutech</b> DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN MM	SCALE: NTS	
SHEET OF	DRAFTING NO.	



THIRD ANGLE PROJECTION 

TITLE/DESCRIPTION  
TAPE-CARR  
TSOP11-32L 32mm

PART NO./I.D. NO.  
CT00033-G-A0085

MATERIAL/MOLD NO.  
STATIC DISSIPATIVE  
POLYSTYRENE

DRAWING NO.  
01-018889

**A** SIZE

APPD. BY

X-2391

ECO NO.  
REV.  
**C**