



**NOTES:**

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3.  $P10 = P_0 \times 10$
4. DIE # WD10280

A <sub>0</sub>	10.30	[.406]
B <sub>0</sub>	20.20	[.795]
K <sub>0</sub>	1.70	[.067]
K <sub>I</sub>	1.20	[.047]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 02-Dec-02
±	CHECKED BY R. BAKER	DATE 10-Dec-02
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	--- CONFIDENTIALITY ---	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY <b>Accutech</b> AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH <b>Accutech</b> WRITTEN CONSENT.	
± 0.5°	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND <b>Accutech</b> DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN MM	SCALE: NTS	
SHEET OF	1 1	

THIRD ANGLE PROJECTION	
TITLE/DESCRIPTION	TAPE - CARR TSOP11-40L 32mm
PART NO./I.D. NO.	CT00034-G-A0097
MATERIAL/MOLD NO.	STATIC DISSIPATIVE POLYSTYRENE
DRAWING NO.	01-019994

APPD. BY **A** SIZE

X-2391

ECO NO. REV. **C**