



NOTES:

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3.  $P10 = P_0 \times 10$
4. DIE # WD20355

A <sub>0</sub>	12.500 [0.492]
B <sub>0</sub>	20.600 [0.811]
K <sub>0</sub>	2.100 [0.083]
K <sub>1</sub>	1.300 [0.051]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 08-Jan-03
±	CHECKED BY R. BAKER	DATE 08-Jan-03
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	--- CONFIDENTIALITY ---	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY <b>Accutech</b> AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH <b>Accutech</b> WRITTEN CONSENT.	
± 0.5°	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND <b>Accutech</b> DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN MM		
SCALE: NTS		
SHEET OF		

THIRD ANGLE PROJECTION

TITLE/DESCRIPTION  
TAPE - CARR  
TSOP11-48L 32mm

PART NO./I.D. NO.  
CT00036-G-A0090

MATERIAL/MOLD NO.  
STATIC DISSIPATIVE  
POLYSTYRENE

DRAWING NO.  
01-020071

**A** SIZE

APPD. BY

X-2391

ECO NO.  
REV.  
**C**