



- NOTES:**
1. EIA-481 STANDARDS APPLY
  2. MATERIAL: STATIC DISSIPATIVE STYRENE
  3. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
  4.  $P10 = P0 \times 10$
  5. DIE NO. W000156

$A_0 = 12.30\text{MM} [0.484]$
$B_0 = 12.30\text{MM} [0.484]$
$K_0 = 1.85\text{MM} [0.073]$

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY R. Baker	DATE 03-Oct-02
±	CHECKED BY .	DATE .
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	--- CONFIDENTIALITY ---	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY <b>Accutech</b> AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH <b>Accutech</b> WRITTEN CONSENT.	
$\sphericalangle \pm 0.5^\circ$	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND <b>Accutech</b> DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN MM	SCALE: NTS	
	SHEET OF	

THIRD ANGLE PROJECTION	
TITLE/DESCRIPTION TAPE-CARR BGA 12X12 24mm	
PART NO./I.D. NO.	CT00044-G-A0100
MATERIAL/MOLD NO.	STATIC DISSIPATIVE POLYSTYRENE
DRAWING NO.	01-018894

A SIZE  
APPD. BY  
X-1649  
ECO NO.  
REV.  
B