



SECTION A-A

- NOTES:
 1. EIA-481 STANDARDS APPLY
 2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
 3. P10=P0 X 10
 4. DIE NO. WD10269

A	= 19.00MM (0.748)
B	= 25.00MM (0.984)
K	= 3.80MM (0.150)
K	= 2.90MM (0.114)

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY R. Baker	DATE 19-Sep-02
±	CHECKED BY .	DATE .
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	--- CONFIDENTIALITY --- THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY Accutech AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH Accutech WRITTEN CONSENT.	
DRAFT UNLESS NOTED:	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND Accutech DRAFTING STANDARD NO. 1.0000.	
±	ALL DIMENSIONS ARE IN MM	
±	SCALE: NTS	
±	SHEET OF	

AccuTechPlastics	
THIRD ANGLE PROJECTION	
TITLE/DESCRIPTION TAPE-CARR QFP 14X20 44mm	
PART NO./I.D. NO.	CT00072-H-A0053
MATERIAL/MOLD NO.	STATIC DISSIPATIVE POLYSTYRENE
DRAWING NO.	01-018671

A SIZE
 APPD. BY
 X-1702
 ECO NO.
 REV.
 B