



DETAIL A  
SCALE 4.000

NOTES:

- EIA-481 STANDARDS APPLY
- POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
- DIE # 9D016

A <sub>o</sub>	11.960 [0.471]
B <sub>o</sub>	15.900 [0.626]
K <sub>o</sub>	10.410 [0.410]
K <sub>1</sub>	9.140 [0.360]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 28-Feb-03
±	CHECKED BY R. BAKER	DATE 28-Feb-03
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	--- CONFIDENTIALITY ---	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY <b>Accutech</b> AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH <b>Accutech</b> WRITTEN CONSENT.	
± 0.5°	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND <b>Accutech</b> DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN MM		
SCALE: NTS		
SHEET OF 1		

		A SIZE APPD. BY
THIRD ANGLE PROJECTION		060 X-990 ECO NO. REV. A
TITLE/DESCRIPTION TAPE - CARR R91834A T-R 32mm		
PART NO./I.D. NO. CT00170-G-A0032		
MATERIAL/MOLD NO. STATIC DISSIPATIVE POLYSTYRENE		
DRAWING NO. 01-020986		