



**DETAIL A**  
SCALE 4.000

**SECTION B-B**

NOTES:

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3.  $P10 = P_0 \times 10$
4. DIE # WD20462

A <sub>0</sub>	24.680 [0.972]
B <sub>0</sub>	34.980 [1.377]
K <sub>0</sub>	2.210 [0.087]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 16-Apr-03
±	CHECKED BY R. BAKER	DATE 16-Apr-03
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	<b>--- CONFIDENTIALITY ---</b>	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY <b>Accutech</b> AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH <b>Accutech</b> WRITTEN CONSENT.	
± 0.5°	<b>UNLESS OTHERWISE NOTED:</b> ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND <b>Accutech</b> DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN MM	SCALE: NTS	
SHEET OF 1	SHEET OF 1	

		A SIZE APPD. BY
THIRD ANGLE PROJECTION		X-1523
TITLE/DESCRIPTION TAPE - CARR R2166C T-R 44mm		
PART NO./I.D. NO. CT00181-G-A0084		
MATERIAL/MOLD NO. STATIC DISSIPATIVE POLYSTYRENE		
DRAWING NO. 01-022077		ECO NO. REV. A