



SECTION B-B

NOTES:

- EIA-481 STANDARDS APPLY
- POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
- $P10 = P_0 \times 10$
- DIE # WD20465

A ₀	13.810 [0.544]
B ₀	13.810 [0.544]
K ₀	4.160 [0.164]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 17-Apr-03
±	CHECKED BY .	DATE .
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	--- CONFIDENTIALITY --- THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY Accutech AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH Accutech WRITTEN CONSENT.	
DRAFT UNLESS NOTED: 0.5°	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND Accutech DRAFTING STANDARD NO. 1.0000.	
± 0.5°	ALL DIMENSIONS ARE IN MM	
SCALE: NTS	SHEET OF 1	

		A SIZE APPD. BY
THIRD ANGLE PROJECTION		X-1594 ECO NO. REV. A
TITLE/DESCRIPTION TAPE - CARR R2282 T-R 24mm		
PART NO./I.D. NO. CT00182-G-A0048		
MATERIAL/MOLD NO. STATIC DISSIPATIVE POLYSTYRENE		
DRAWING NO. 01-022109		