



NOTES:

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3. $P10 = P_0 \times 10$
4. DIE # WD20469

A ₀	13.550 [0.533]
B ₀	13.550 [0.533]
K ₀	2.100 [0.083]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. VALENTINE	DATE 19-MAY-03
±	CHECKED BY R. BAKER	DATE 28-MAY-03
±	DESIGNED BY K. WAGNER	DATE 19-MAY-03
±	APPROVED BY R. BAKER	DATE 28-MAY-03
±	--- CONFIDENTIALITY ---	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY Accutech AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH Accutech WRITTEN CONSENT.	
± 0.5°	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND Accutech DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN MM	SCALE: NTS	
SHEET OF	1	

Accu-Tech Plastics

THIRD ANGLE PROJECTION

TITLE/DESCRIPTION
TAPE - CARR
BGA 13x13 24mm

PART NO./I. D. NO.
CT00186-G-A0088

MATERIAL/MOLD NO.
STATIC DISSIPATIVE
POLYSTYRENE

DRAWING NO.
01-022632

A SIZE
APPD. BY

X-2490

ECO NO.
REV.
B