



NOTES:

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3.  $P10 = P0 \times 10$
4. DIE # WD20476

A <sub>0</sub>	14.550 [0.573]
B <sub>0</sub>	14.550 [0.573]
K <sub>0</sub>	2.100 [0.083]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. VALENTINE	DATE 20-MAY-03
±	CHECKED BY R. BAKER	DATE 28-MAY-03
±	DESIGNED BY K. WAGNER	DATE 19-MAY-03
±	APPROVED BY R. BAKER	DATE 28-MAY-03
±	--- CONFIDENTIALITY --- THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY <b>Accutech</b> AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH <b>Accutech</b> WRITTEN CONSENT.	
DRAFT UNLESS NOTED: 0.5°	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND <b>Accutech</b> DRAFTING STANDARD NO. 1.0000.	
± 0.5°	SCALE: NTS	
ALL DIMENSIONS ARE IN MM	SHEET OF 1	

		THIRD ANGLE PROJECTION
TITLE/DESCRIPTION TAPE - CARR BGA 14x14 24mm		
PART NO./I.D. NO. CT00193-G-A0088		X-2490
MATERIAL/MOLD NO. STATIC DISSIPATIVE POLYSTYRENE		
DRAWING NO. 01-022688		
APPD. BY		A SIZE
ECO NO. REV.		B