



NOTES:

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3. $P10 = P0 \times 10$
4. DIE # WD20477

A ₀	15.550 [0.612]
B ₀	15.550 [0.612]
K ₀	2.100 [0.083]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. VALENTINE	DATE 20-MAY-03
±	CHECKED BY R. BAKER	DATE 28-MAY-03
±	DESIGNED BY K. WAGNER	DATE 20-MAY-03
±	APPROVED BY R. BAKER	DATE 28-MAY-03
±	--- CONFIDENTIALITY ---	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY Accutech AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH Accutech WRITTEN CONSENT.	
± 0.5°	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND Accutech DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN MM	SCALE: NTS	
SHEET OF	1	

		A SIZE APPD. BY
THIRD ANGLE PROJECTION		X-2491
TITLE/DESCRIPTION TAPE - CARR BGA 15x15 24mm		
PART NO./I.D. NO. CT00194-G-A0088		
MATERIAL/MOLD NO. STATIC DISSIPATIVE POLYSTYRENE		
DRAWING NO. 01-022689		ECO NO. REV. B