



NOTES:

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3.  $P10 = P0 \times 10$
4. DIE # WD20486

A <sub>0</sub>	23.930 [0.942]
B <sub>0</sub>	39.320 [1.548]
K <sub>0</sub>	2.925 [0.115]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 14-May-03
±	CHECKED BY R. BAKER	DATE 15-May-03
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	--- CONFIDENTIALITY ---	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY <b>Accutech</b> AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH <b>Accutech</b> WRITTEN CONSENT.	
± 0.5°	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND <b>Accutech</b> DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN MM		
SCALE: NTS		
SHEET OF 1		

		A SIZE APPD. BY
THIRD ANGLE PROJECTION		X-2336 ECO NO. REV. B
TITLE/DESCRIPTION TAPE - CARR R2285A T-R 56mm		
PART NO./I.D. NO. CT00205-G-A0067		
MATERIAL/MOLD NO. STATIC DISSIPATIVE POLYSTYRENE		
DRAWING NO. 01-022581		