



SECTION B-B

NOTES:

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3. $P10 = P_0 \times 10$
4. DIE # WR000007

5. NUMBER IDENTIFIES PRODUCT CONFIGURATION. FOR COMPLETE ORDER NUMBER TO INCLUDE MATERIAL TYPE AND QUANTITY PER REEL, CONTACT CUSTOMER SERVICE.

USER DIRECTION OF UNREELING →

1	2
3	4

PIN 1 LOCATION

A ₀	1.778 [0.070]
B ₀	1.874 [0.074]
K ₀	0.928 [0.037]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 12-Mar-03
±	CHECKED BY .	DATE .
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	--- CONFIDENTIALITY ---	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY Accutech AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH Accutech WRITTEN CONSENT.	
± 0.5°	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND Accutech DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN MM	SCALE: NTS	
1 SHEET OF 1		

AccuTechPlastics		A SIZE APPD. BY
THIRD ANGLE PROJECTION		X-2912
TITLE/DESCRIPTION TAPE - CARR SC90 (super mini) 8mm		ECO NO. REV.
PART NO./I.D. NO. CT00222 5.		A
MATERIAL/MOLD NO. SEE NOTE 5.		
DRAWING NO. 01-021469		