


**NOTES:**

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3. P10=P0 X 10
4. DIE # WR000010
5. NUMBER IDENTIFIES PRODUCT CONFIGURATION. FOR COMPLETE ORDER NUMBER TO INCLUDE MATERIAL TYPE AND QUANTITY PER REEL, CONTACT CUSTOMER SERVICE.

USER DIRECTION OF UNREELING →



PIN 1 LOCATION

A <sub>0</sub>	2.286 [0.090]
B <sub>0</sub>	2.262 [0.089]
K <sub>0</sub>	1.124 [0.044]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 24-Mar-03
±	CHECKED BY P. MUELLER	DATE 24-Mar-03
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	<b>--- CONFIDENTIALITY ---</b>	
DRAFT UNLESS NOTED: 0.5°	THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY <b>Accutech</b> AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH <b>Accutech</b> WRITTEN CONSENT.	
± 0.5°	<b>UNLESS OTHERWISE NOTED:</b> ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND <b>Accutech</b> DRAFTING STANDARD NO. 1.0000.	
ALL DIMENSIONS ARE IN MM	SCALE: NTS	
1 SHEET OF 1		

THIRD ANGLE PROJECTION	
TITLE/DESCRIPTION TAPE - CARR SOT326 8mm	
PART NO./I.D. NO.	CT00223
MATERIAL/MOLD NO.	SEE NOTE
DRAWING NO.	01-021653

**A** SIZE  
 APPD. BY  
 X-2912  
 ECO NO.  
 REV.  
**A**