



NOTES:

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3. $P10 = P_0 \times 10$
4. DIE # WD20491

A ₀	39.980 [1.574]
B ₀	42.480 [1.672]
K ₀	4.030 [0.159]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 10-Jul-03		A SIZE APPD. BY
±	CHECKED BY .	DATE .		
±	DESIGNED BY .	DATE .		
±	APPROVED BY .	DATE .		
±	--- CONFIDENTIALITY --- THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY Accutech AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH Accutech WRITTEN CONSENT.			
DRAFT UNLESS NOTED: 0.5°	ALL DIMENSIONS ARE IN MM SCALE: NTS		THIRD ANGLE PROJECTION 	X-2286 ECO NO. REV.
$\nabla \pm 0.5^\circ$	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND Accutech DRAFTING STANDARD NO. 1.0000.		TITLE/DESCRIPTION TAPE - CARR 5051-62 56mm	
ALL DIMENSIONS ARE IN MM	PART NO./I.D. NO. CT00234-G-A0045		MATERIAL/MOLD NO. STATIC DISSIPATIVE POLYSTYRENE	
SCALE: NTS	DRAWING NO. 01-023334			
1 SHEET OF 1				