



NOTES:

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3. $P10 = P_0 \times 10$
4. DIE # WD20493

Ao	23.180 [0.913]
Bo	36.360 [1.431]
Ko	2.240 [0.088]

TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY K. WAGNER	DATE 14-Jul-03
±	CHECKED BY WDH	DATE 14-Jul-03
±	DESIGNED BY .	DATE .
±	APPROVED BY .	DATE .
±	--- CONFIDENTIALITY --- THIS DRAWING IS HEREBY DESIGNATED AS CONFIDENTIAL. INFORMATION ON IT IS PROPRIETARY Accutech AND SHALL NOT BE USED OR DISCLOSED TO THIRD PERSONS EXCEPT IN CONFORMITY WITH Accutech WRITTEN CONSENT.	
DRAFT UNLESS NOTED: 0.5°	UNLESS OTHERWISE NOTED: ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994 AND Accutech DRAFTING STANDARD NO. 1.0000.	
± 0.5°	SCALE: NTS	
ALL DIMENSIONS ARE IN MM	SHEET OF 1	

AccuTechPlastics		A SIZE APPD. BY
THIRD ANGLE PROJECTION		X-2301
TITLE/DESCRIPTION TAPE - CARR R2307 T-R 56mm		ECO NO. REV.
PART NO./I.D. NO. CT00236-G-A0075		A
MATERIAL/MOLD NO. STATIC DISSIPATIVE POLYSTYRENE		
DRAWING NO. 01-023355		