



NOTES:

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3. $P10 = P_0 \times 10$
4. DIE # WD20511

| | |
|----------------|----------------|
| A ₀ | 32.310 [1.272] |
| B ₀ | 39.540 [1.557] |
| K ₀ | 2.830 [0.111] |

| | | | | |
|---|-----------------------|-------------------|---|------------------------|
| IMPORTANT NOTICE: | | | | A SIZE |
| DRAWING DOES NOT CONTAIN ALL DIMENSIONS, SPECIFICATIONS, AND TOLERANCES. THIS DRAWING IS INTENDED TO ASSIST THE CUSTOMER IN DESIGNING AN INTERFACE MODULE BETWEEN THE CUSTOMER'S EQUIPMENT AND Accutech PRODUCT/EQUIPMENT. ALL DIMENSIONS AND TOLERANCES IF DEFINED ARE PER ASME Y14.5M - 1994 | | | | THIRD ANGLE PROJECTION |
| NOTE: ALL DIMENSIONS ARE CONSIDERED CRITICAL. | | | DESCRIPTION | X-3023 |
| | | | TAPE - CARR R2285B T-R 56mm | |
| | | | PART NO. CT00265-G-A0060 | |
| | | | MATERIAL STATIC DISSIPATIVE POLYSTYRENE | |
| ALL DIMENSIONS ARE IN MILLIMETERS | DRAWN BY K. WAGNER | DATE 18-Sep-03 | DRAWING NO. 01-024258 | ECO NO. REV. A |
| DO NOT SCALE | SHEET 1 OF 1 | | | |