



NOTES:

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3.  $P10 = P_0 \times 10$
4. DIE # WD20516

A <sub>0</sub>	25.610 [1.008]
B <sub>0</sub>	37.440 [1.474]
K <sub>0</sub>	2.240 [0.088]

<b>IMPORTANT NOTICE:</b>				<b>A</b> SIZE
DRAWING DOES NOT CONTAIN ALL DIMENSIONS, SPECIFICATIONS, AND TOLERANCES. THIS DRAWING IS INTENDED TO ASSIST THE CUSTOMER IN DESIGNING AN INTERFACE MODULE BETWEEN THE CUSTOMER'S EQUIPMENT AND <b>Accutech</b> PRODUCT/EQUIPMENT. ALL DIMENSIONS AND TOLERANCES IF DEFINED ARE PER ASME Y14.5M - 1994				THIRD ANGLE PROJECTION
NOTE: ALL DIMENSIONS ARE CONSIDERED CRITICAL.			DESCRIPTION	X-3520
			TAPE - CARR R2307B T-R 56mm	
			PART NO. CT00277-G-A0075	
			MATERIAL STATIC DISSIPATIVE POLYSTYRENE	
ALL DIMENSIONS ARE IN MILLIMETERS	DRAWN BY K. ANDERSON	DATE 07-Nov-03	DRAWING NO. 01-025006	ECO NO. REV. <b>A</b>
DO NOT SCALE	SHEET 1 OF 1			