



NOTES:

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3. $P10 = P_0 \times 10$

4. NUMBER IDENTIFIES PRODUCT CONFIGURATION. FOR COMPLETE ORDER NUMBER TO INCLUDE MATERIAL TYPE AND QUANTITY PER REEL, CONTACT CUSTOMER SERVICE.

| | |
|----------------|------------------------|
| A ₀ | 2.79±0.10 [0.110±.004] |
| B ₀ | 3.51±0.10 [0.138±.004] |
| K ₀ | 1.52±0.10 [0.060±.004] |

| | | | | |
|---|-------------------------|--------------------------|------------------------|-----------|
| IMPORTANT NOTICE: | | | THIRD ANGLE PROJECTION | A SIZE |
| DRAWING DOES NOT CONTAIN ALL DIMENSIONS, SPECIFICATIONS, AND TOLERANCES. THIS DRAWING IS INTENDED TO ASSIST THE CUSTOMER IN DESIGNING AN INTERFACE MODULE BETWEEN THE CUSTOMER'S EQUIPMENT AND Accutech PRODUCT/EQUIPMENT. ALL DIMENSIONS AND TOLERANCES IF DEFINED ARE PER ASME Y14.5M - 1994 | | | | |
| NOTE: ALL DIMENSIONS ARE CONSIDERED CRITICAL. | | PART NO. CT00380 | X-9612 | |
| ALL DIMENSIONS ARE IN MILLIMETERS [INCHES] | DRAWN BY K. ANDERSON | MATERIAL SEE NOTE | | |
| DO NOT SCALE | DATE 11-May-04 | DRAWING NO. 01-027181 | B | |
| SHEET 1 OF 1 | | | | |