



NOTES:

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3. $P_{10} = P_0 \times 10$

4. NUMBER IDENTIFIES PRODUCT CONFIGURATION. FOR COMPLETE ORDER NUMBER TO INCLUDE MATERIAL TYPE AND QUANTITY PER REEL, CONTACT CUSTOMER SERVICE.

Ao	10.76 ± 0.10 [0.424±.004]
Bo	11.27 ± 0.10 [0.444±.004]
Ko	9.16 ± 0.10 [0.361±.004]
KI	8.16 ± 0.10 [0.321±.004]

IMPORTANT NOTICE:				A SIZE
DRAWING DOES NOT CONTAIN ALL DIMENSIONS, SPECIFICATIONS, AND TOLERANCES. THIS DRAWING IS INTENDED TO ASSIST THE CUSTOMER IN DESIGNING AN INTERFACE MODULE BETWEEN THE CUSTOMER'S EQUIPMENT AND Accutech PRODUCT/EQUIPMENT. ALL DIMENSIONS AND TOLERANCES IF DEFINED ARE PER ASME Y14.5M - 1994				THIRD ANGLE PROJECTION
NOTE: ALL DIMENSIONS ARE CONSIDERED CRITICAL.			DESCRIPTION	X-10332
			TAPE - CARR 26PC01SMT 24mm	
			PART NO. CT00429	
			MATERIAL SEE NOTE	
ALL DIMENSIONS ARE IN MILLIMETERS [INCHES]	DRAWN BY K. ANDERSON	DATE 21-Jan-05	DRAWING NO. 01-030617	ECO NO. REV. B
DO NOT SCALE	SHEET 1 OF 1			