



**SECTION B-B**

**NOTES:**

1. EIA-481 STANDARDS APPLY
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3.  $P_{10} = P_0 \times 10$

4. NUMBER IDENTIFIES PRODUCT CONFIGURATION. FOR COMPLETE ORDER NUMBER TO INCLUDE MATERIAL TYPE AND QUANTITY PER REEL, CONTACT CUSTOMER SERVICE.

Ao	27.55±0.10 [1.085±.004]
Bo	17.00±0.10 [0.669±.004]
Ko	7.05±0.10 [0.278±.004]
K1	0.80±0.10 [0.031±.004]

**IMPORTANT NOTICE:**

DRAWING DOES NOT CONTAIN ALL DIMENSIONS, SPECIFICATIONS, AND TOLERANCES. THIS DRAWING IS INTENDED TO ASSIST THE CUSTOMER IN DESIGNING AN INTERFACE MODULE BETWEEN THE CUSTOMER'S EQUIPMENT AND **Accutech** PRODUCT/EQUIPMENT. ALL DIMENSIONS AND TOLERANCES IF DEFINED ARE PER ASME Y14.5M - 1994

NOTE: ALL DIMENSIONS ARE CONSIDERED CRITICAL.

ALL DIMENSIONS ARE IN MILLIMETERS [INCHES]

DO NOT SCALE

DRAWN BY: K. ANDERSON  
DATE: 23-Mar-05

SHEET 1 OF 1

**Accu-Tech**Plastics

THIRD ANGLE PROJECTION

DESCRIPTION: TAPE - CARR  
70708390 SHIELD 32mm

PART NO.: CT00453 4

MATERIAL: SEE NOTE 4.

DRAWING NO.: 01-031700

A SIZE

X-12303

ECO NO. REV. B